	<p align="center">SPECIFICATION YTTERBIUM LASER SYSTEM Model YLS-12000</p>	Spec: Revision: Issue date: Page:	G22-15253090 -- 23.07.2020 1 of 3
---	---	--	--

1. Optical characteristics

N	Characteristics	Test conditions	Symbol	Min.	Typ.	Max.	Unit
1	Operation Mode			CW / Modulated			
2	Polarization			Random			
3	Nominal Output Power		P_{nom}	12000			W
4	Output Power Tuning Range			10		105	%
5	Emission Wavelength	Output power: 12000 W	λ	1068		1080	nm
6	Emission Linewidth	Output power: 12000 W	$\Delta\lambda$		3	6	nm
7	Switching ON/OFF Time	Output power: 12000 W			50	100	μ s
8	Output Power Modulation Rate	Output power: 12000 W				5	kHz
9	Output Power Instability	Output power: 12000 W Time interval: 1 hour (T=Constant)			± 1	± 2	%
10	Red Guide Laser Power				0.4	0.5	mW

2. Optical output


N	Characteristics	Test conditions	Symbol	Min.	Typ.	Max.	Unit
1	Process Fiber Connector			HLC-16			
2	Beam Parameter Product* (86 %)	Delivery fiber core diameter 100 μ	BPP*		3.5	4.2	mm*mrad
3	Beam Parameter Product* (86 %)	Delivery fiber core diameter 150 μ	BPP*		5.5	6.5	mm*mrad
4	Beam Parameter Product* (86 %)	Delivery fiber core diameter 200 μ	BPP*		6.5	8.5	mm*mrad
5	Process Fiber Length		L	10	20	30**	m
6	Process Fiber Bending Radius - unstressed - stressed		R	100 200			mm

* Measurement accuracy by means of Primes Focus Monitor ± 10 %

**Maximal delivery fiber length is 35 m @ 100 μ for laser operation with IPG Photonics cutting head, part number CDT3HS1020HXXPXU.

CONFIDENTIAL: This document and any data disclosed therein is the property of IPG Photonics Corporation and its affiliates, and constitute and contain proprietary information. Neither receipt nor possession of this document confers or transfers any right to duplicate, use, or disclose any information contained herein except as expressly authorized in writing by IPG Photonics Corporation. No representations and warranties are made hereby, except in a binding purchase order.

YLS-12000 specification G22-15253090.docx

	<p align="center">SPECIFICATION YTTERBIUM LASER SYSTEM Model YLS-12000</p>	Spec: Revision: Issue date: Page:	G22-15253090 -- 23.07.2020 2 of 3
--	---	--	--

3. General characteristics

N	Characteristics	Min.	Typ.	Max.	Unit
1	Operating Ambient Temperature Range	5		45	°C
2	Humidity, Ambient Temperature Range $\leq 40^{\circ}\text{C}$	10		95	%
3	Storage Temperature without water	- 40		+ 75	°C
4	Dimensions (w/o interface plugs, w/o castors), WxDxH	1004(1007) x 815 x 806			mm
5	Weight		400		kg

4. Cooling


N	Characteristics	Test conditions	Symbol	Min.	Typ.	Max.	Unit
1	Method			Tap and slightly DI-water			
2	Cooling Water Temperature for Laser			20	21	22	°C
3	Cooling Water Temperature for Optics			27	30	33	°C
4	Laser "Cold Start" Temperature			20			°C
5	Optics cooling water conductivity			30	40	50	$\mu\text{S}/\text{cm}$
6	Water Pressure			1.4	2.5	3.5	bar
7	Water Flow for Laser Cooling			2.5		3.5	l/min
8	Water Flow for Fiber Connector Cooling			70	100		l/min
9	Chiller Cooling Capacity			22.5			kW

5. Electrical characteristics

N	Characteristics	Min.	Typ.	Max.	Unit
1	Operating Voltage, 3 phases	400-460 V/3P + PE @ 50-60 Hz			
2	Laser Power Consumption at 12000 W power			34.5	kW
3	Laser Operation Current at 12000 W power and 400 VAC			53.2	A
4	Input fuses, 400 VAC			63	A

6. Fast power supply option.

- Switching OFF of laser main power supplies during 130 msec accordingly Category 3 PL d EN ISO 13849-1
- Maximal quantity of main power supplies switching ON/OFF cycles per minute is 20 times.

	<p align="center">SPECIFICATION YTTERBIUM LASER SYSTEM Model YLS-12000</p>	<p>Spec: Revision: Issue date: Page:</p>	<p align="center">G22-15253090 -- 23.07.2020 3 of 3</p>
--	---	---	--

7. Laser External Layout

