

	<b>PRODUCT SPECIFICATION</b> <b>YTTERBIUM LASER SYSTEM</b> <b>Model YLS-10000-U-Y20</b>	Spec:	G22-2530302
		Revision:	--
		Date:	19.02.2020
		Page:	1 of 3

## 1. Optical characteristics

N	Characteristics	Test conditions	Symbol	Min.	Typ.	Max.	Unit
1	Operation Mode			CW / Modulated			
2	Polarization			Random			
3	Nominal Output Power		$P_{nom}$	10000			W
4	Output Power Tuning Range			10		105	%
5	Emission Wavelength	Output power: 10000 W	$\lambda$	1068		1080	nm
6	Emission Linewidth	Output power: 10000 W	$\Delta\lambda$		3	6	nm
7	Switching ON/OFF Time	Output power: 10000 W			50	100	$\mu$ s
8	Output Power Modulation Rate	Output power: 10000 W				5	kHz
9	Output Power Instability	Output power: 10000 W Time interval: 8 hrs (T=Constant)			$\pm 1$	$\pm 2$	%
10	Red Guide Laser Power				0.4	0.5	mW

## 2. Optical output

N	Characteristics	Test conditions	Symbol	Min.	Typ.	Max.	Unit
1	Delivery Fiber Connector			HLC-8, QBH-compatible LCA, QD-compatible Option: HLC-16			
2	Beam Parameter Product* (86 %)	Delivery fiber core diameter 100 $\mu$	BPP*		3.3	4.0	mm*mrad
3	Beam Parameter Product* (86 %)	Delivery fiber core diameter 150 $\mu$	BPP*		5.0	6.0	mm*mrad
4	Beam Parameter Product* (86 %)	Delivery fiber core diameter 200 $\mu$	BPP*		6.0	8.0	mm*mrad
5	Delivery Fiber Length**		L	10	20**	30	m
6	Delivery Fiber Bending Radius - unstressed - stressed		R	100 200			mm

\* Measurement accuracy by means of Primes Focus Monitor  $\pm 10\%$

\*\*Maximal delivery fiber length is 25 m @ 100  $\mu$

**CONFIDENTIAL:** This document and any data disclosed therein is the property of IPG Photonics Corporation and its affiliates, and constitute and contain proprietary information. Neither receipt nor possession of this document confers or transfers any right to duplicate, use, or disclose any information contained herein except as expressly authorized in writing by IPG Photonics Corporation. No representations and warranties are made hereby, except in a binding purchase order.

YLS-10000-U-Y20 specification G22-2530302.docx

	<b>PRODUCT SPECIFICATION</b> <b>YTTERBIUM LASER SYSTEM</b> <b>Model YLS-10000-U-Y20</b>	Spec:	G22-2530302
		Revision:	--
		Date:	19.02.2020
		Page:	2 of 3

### 3. General characteristics

N	Characteristics	Min.	Typ.	Max.	Unit
1	Operating Ambient Temperature Range	5		45	°C
2	Humidity, Ambient Temperature Range ≤ 40°C	10		95	%
3	Storage Temperature without water	- 40		+ 75	°C
4	Dimensions (w/o interface plugs, w/o castors), WxDxH:	430 x 808 x 900			mm
5	Weight		240		kg

### 4. Cooling


N	Characteristics	Test conditions	Min.	Typ.	Max.	Unit
1	Method		Tap and slightly DI-water			
2	Cooling Water Temperature for Laser		20	21	22	°C
3	Cooling Water Temperature for Optics		27	30	33	°C
4	Laser “Cold Start” Temperature		20			°C
5	Optics cooling water conductivity		30	40	50	μS/cm
6	Water Pressure		2.5		3.5	bar
7	Water Flow for Laser Cooling		60	80		l/min
8	Fiber Connector Cooling Water Flow Rate		1.0	1.5	2.5	l/min

### 5. Electrical characteristics

N	Characteristics	Min.	Typ.	Max.	Unit
1	Operating Voltage, 3 phases	400-460 V/3P + PE @ 50-60 Hz			
2	Laser Power Consumption at 10000 W power		25	28	kW
3	Laser Operation Current at 10000 W power and 400 VAC			48	A
4	Input fuses, 400 V			60	A

### 6. Fast power supply option.

- 6.1. Switching OFF of laser main power supplies during 130 msec accordingly Category 3 PL d EN ISO 13849-1
- 6.2. Maximal quantity of main power supplies switching ON/OFF cycles per minute is 20 times.



**PRODUCT SPECIFICATION  
YTTERBIUM LASER SYSTEM  
Model YLS-10000-U-Y20**

Spec:	G22-2530302
Revision:	--
Date:	19.02.2020
Page:	3 of 3

## 7. External layout

